

THERMOCLAVE®

LTM™ 20

Environment-Friendly

Portable Electric Heater

**Ideal for treatment areas from
400-600 sq. ft.**

**Residential spaces, small
commercial spaces, larger
hotel / motel rooms**



- Heat controlled by a solid state relay
- Thermal overload protection
- High quality tube axel fan with ball bearings for lowest noise and longest life
- Corrosion resistant galvanized steel enclosure
- 50 Amp twist lock electrical connection
- Dual discharge air temperature 125° F / 155° F set point
- Built in electronic temperature controller and sensor proportionally modulates the heating load to match the exact capacity required for energy efficient operation
- Temperature sensor controls the heater proportionally to maintain the pre-set air discharge temperature
- Open coil elements made of the highest grade nickel-chrome resistance wire will not age or oxidize, thus assuring longer heater life

Capacity	Maximum (BTU/Hr)	Maximum Outlet Temperature	Maximum Air Flow (CFM)	Voltage	AMP Rating	Overall Dimensions (L x W x H)	Weight (lbs)
20 kW	61,400	155° F	1,200	480 V 3 Phase	24.06	44" x 24" x 27"	146



www.ZapBugsNow.com
www.OnSiteMfg.com
sales@onsitemfg.com
Toll Free: 866.935.6764