

THERMOCLAVE®

LTM™ 9

Environment-Friendly Portable Electric Heater



**Ideal for treatment areas up to 300 square feet
Hotel / motel rooms, dorm rooms, self storage units and pods,
larger vehicles such as shuttle buses, vans, panel trucks**

- Heat controlled by a solid state relay
- Thermal overload protection
- High quality tube axial fan with ball bearings for lowest noise and longest life
- Corrosion resistant galvanized steel enclosure
- NEMA style 6 - 50P Plug
- Dual discharge air temperature 125° F / 155° F set point
- Discharge air duct
- Built-in electronic temperature controller and sensor proportionally modulates the heating load to match the exact capacity required for energy efficient operation
- Temperature sensor controls the heater proportionally to maintain the pre-set air discharge temperature
- Open coil elements made of the highest grade nickel-chrome resistance wire will not age or oxidize, thus assuring longer heater life

| Capacity | Maximum (BTU/Hr) | Maximum Outlet Temperature | Maximum Air Flow (CFM) | Voltage | AMP Rating | Unit Dimensions (without discharge air duct) (L x W x H) | Weight (lbs) |
|----------|------------------|----------------------------|------------------------|--------------------------|------------|--|--------------|
| 9 kW | 30,717 | 155° F | 300 | 208 / 240V Single Phase* | 37.5 | 28.5" x 15" x 16.75" (incl. 1.75" handles) | 54 |

* Three power circuit model available



www.ZapBugsNow.com
www.OnSiteMfg.com
sales@onsitemfg.com
Toll Free: 866.935.6764